

Surface-Mount Housing (GA 612-...)



Product Details

Surface-mount housing in extruded sectional aluminum with die-cast zinc corner connections and steel sheet floor plate, with complete powder / paintwork coating. To hold info sign modules ISM 611-..., surface-area luminaries LM 611-..., ambient luminaries VL 611-...1-.. and mounting frame MR 611-...

Quick-release fasteners are available for fixture of the mounting frame MR 611-...

Mounting frame MR 611-.. is not required for fixture of the info sign and surface area / ambient luminaries in surface-mount housings.

The housing units are suitable for vertical or horizontal mounting and are fixed to the wall with the aid of 4 fixing holes. For the insertion of cables, depending on size there are one or more cable inlet openings available with relevant cable clamps and the corresponding number of seals against the egress of water. The two and three-tier surface-mount housing are additionally fitted with cable channels to ensure tidy installation.

With integrated catches for quick fastening of the combination terminals.

Specifications:

Part Number	Vario Modules	Dimensions (W x H x D)	Weight (Ounces)
GA 612-1/1-0	1 x 1	5.2" x 6.3" x 1.4"	21
GA 612-2/1-0	2 x 1	5.2" x 9.1" x 1.4"	27
GA 612-3/1-0	3 x 1	5.2" x 13" x 1.4"	35
GA 612-4/1-0	4 x 1	5.2" x 16.9" x 1.4"	42
GA 612-5/1-0	5 x 1	5.2" x 20.8" x 1.4"	
GA 612-2/2-0	2 x 2	9.1" x 9.1" x 1.4"	39
GA 612-3/2-0	3 x 2	9.1" x 13" x 1.4"	51
GA 612-4/2-0	4 x 2	9.1" x 16.9" x 1.4"	67
GA 612-3/3-0	3 x 3	13" x 13" x 1.4"	68
GA 612-4/3-0	4 x 3	13" x 16.9" x 1.4"	84