



Product description

Access camera module 80 for installation in Siedle Vario 611 housing and the Siedle Access intercom system.

Performance features:

- Integrated heating with 2-stage temperature control
- Infrared lighting and control electronics
- Colour system PAL
- Image pick-up CMOS sensor 8.4 mm (1/3") 720 x 480 pixel (horizontal/vertical)
- Lens attachment 2.9 mm
- Pick-up angle horizontal 80°, vertical 60°
- Additional mechanical adjustment range 30° horizontal and vertical
- Horizontal resolution 500 TV-lines

Specifications

| | |
|----------------------------|------------------|
| Protection system: | IP 54, IK 10 |
| Ambient temperature: | -20 °C to +55 °C |
| Height of structure (mm): | 32 |
| Dimensions (mm) W x H x D: | 99 x 99 x 58 |

Article information

| Article designation | Article description | Colour/Material | Article no. |
|---------------------|----------------------|---------------------|-------------|
| ACM 670-01 BG | Access camera module | Micaceous amber | 048115 |
| ACM 670-01 DG | Access camera module | Micaceous dark grey | 048116 |
| ACM 670-01 SH | Access camera module | High gloss black | 048114 |
| ACM 670-01 SM | Access camera module | Silver metallic | 048112 |
| ACM 670-01 W | Access camera module | White | 048111 |
| ACM 670-01 WH | Access camera module | High gloss white | 048113 |

Access camera module
ACM 670-01

Page 2





| | | | |
|------------------------------------|---------------------------|--------|--------------------------|
| ACM 670-01 Access camera module | Product information | 756 kB | Download |
| ACM 670-0 Access camera module | Product information | 1,1 MB | Download |
| ACM 670-0/-02 Access camera module | Declaration of Conformity | 620 kB | Download |