



## Product description

The bus video demodulator converts the video signal from the In-Home bus into an FBAS signal, so that customarily available video monitors, video surveillance systems and TVs (with AV input) can display the picture.

As long as control voltage is applied at the control input, the FBAS video signal is available at the video output. In addition, the potential-free output is closed for this period. No continuous monitoring is possible in the In-Home bus for system-related reasons.

## Specifications


Operating voltage:	12 V AC, max. 300 mA
Control voltage / current:	4–30 V DC, max. 10 mA 4–20 V AC, max. 5 mA
Contact type:	n.o. contact max. 30 V AC/DC, 2 A
Protection system:	IP 20
Ambient temperature:	0 °C to +40 °C
Horizontal pitch (HP):	6
Dimensions (mm) W x H x D:	107 x 89 x 60

## Article information

Article designation	Article description	Colour/Material	Article no.
BVD 650-0	Bus video demodulator	Black	039801

Bus video demodulator  
BVD 650-0

Page 2



---


## Accessories


---

Article designation	Article description	Colour/Material	Article no.
ZAP 6-0	Accessory terminal cover	Black	105205

Bus video demodulator  
BVD 650-0

Page 3





---

BVD 650-0 Bus video demodulator

Product information

622 kB

[Download](#)

Declaration of Conformity

290 kB

[Download](#)