



Product description

P.O. amplifier unit in a switch panel housing.

Electronic circuit for adjustment to a TC system with interface to FTZ 123 D12, 2 volume levels for speech directions door - TC system and TC system - door; potential-free contact for actuation of an external bell. Can only be used a wire-saving system with TLM 612-..., TLM 512-... or TLE 061-... Surface mounting with terminal cover ZAP 502-0.

Specifications

Operating voltage:	10–15 V AC or 15–24 V DC
Operating current:	max. 35 mA
Contact type:	24 V, 2 A, AC/DC
Ambient temperature:	0 °C to +40 °C
Horizontal pitch (HP):	3
Protection system:	IP 20
Dimensions (mm) W x H x D:	53.5 x 89 x 60

Article information

Article designation	Article description	Colour/Material	Article no.
PVG 602-01	P.O. amplifier unit	Black	221140



Accessories

Article designation	Article description	Colour/Material	Article no.
ZAP 3-0	Accessory terminal cover	Black	113442

P.O. amplifier unit
PVG 602-01

Page 3



P.O. amplifier unit
PVG 602-01

Page 4



PVG 602-01 P.O.amplifier unit
PVG 602-...

Product information

610 kB

[Download](#)

Declaration of Conformity

385 kB

[Download](#)