



Product description

Select letterbox video. Letterbox with integrated video door communication. Plastic housing with solid aluminium front, for surface-mounting. Removal from the front, with newspaper compartment. In compliance with DIN EN 13724.

Video door station with integrated illuminated light button, call button with backlit nameplate, exchangeable from the front, and colour CCD camera.

- Colour system PAL
- Image pick-up CCD sensor 8.4 mm (1/3") 752 x 582 pixel (horizontal/vertical)
- Lens 3.7 mm
- Automatic day/night switchover
- Horizontal pick-up angle appr. 60°, vertical appr. 50°
- Additional mechanical adjustment range by appr. 30° on the horizontal and vertical
- Horizontal resolution 450 lines
- Integrated infrared lighting
- 2-stage heating 12 V AC max. 100 mA

Specifications

Nameplate size (mm) W x H:	56 x 56
Pass-through size (mm) W x H:	331 x 31.6
Call button (mm) W x H:	59 x 59
Protection system:	IP 54, IK 8
Ambient temperature:	-20 °C to +40 °C
Dimensions (mm) W x H x D:	409 x 645 x 125

Article information

Article designation	Article description	Colour/Material	Article no.
SBV 850-0 A	Select letterbox video	Aluminium	040551
SBV 850-0 W	Select letterbox video	White	038098



Select letterbox video
SBV 850-0

Page 2

Accessories

Article designation	Article description	Colour/Material	Article no.
Vario 611 W	Repair paint	White	039936

Spare parts

Article designation	Article description	Colour/Material	Article no.
CA/CV 812/850-...STA/STV 850-...	Loudspeaker	Miscellaneous	029867
CSA/CSV/STA/STV 850-...	Microphone	Miscellaneous	029820
CSA/CSV/STA/STV 850-1	Nameplate superstructure	Clear glass	029816
CSA/CSV/STA/STV 850-1	Nameplate insert	White	029813
SB 800-...,SBA/SBV 850-...	Spare lock	Miscellaneous	029541

Select letterbox video
SBV 850-0

Page 3





Select letterbox video
SBV 850-0

Page 4

SBV 850-0 Select letterbox video	Product information	2,7 MB	Download
SBV 850-0 Select letterbox video	Product information	1,2 MB	Download
SBV 850-0 Select letterbox video	Declaration of Conformity	335 kB	Download