



Product description

Switching/remote controller in switch panel housing for execution of max. 4 central switching/control functions (connection to DL) or 4 local switching/control functions (connection GC 612-... or door loudspeaker of the ETC 602-...).

1 relay with changeover contact and 3 relays with 1 working contact each. Actuation takes place from buttons 1-5, light and door release of the HTC 811-... From the HTS 811-..., only the light and door release buttons can be used. Function of buttons 1-5 can be set via DIL switches as switches or buttons. For use as timer, e.g. to trigger a heavy current relay for staircase lighting. Connection facility to ETC 602-..., GC 612-..., TLE 061-... and TLM 612-...

Specifications

| | |
|----------------------------|--|
| Operating voltage: | 12 V AC |
| Operating current: | max. 250 mA |
| Contact type: | 1 changeover switch 24 V DC/AC, 2 A; 3 n.o. contacts 24 V DC/AC, 2 A |
| Switching time: | 2 x adjustable from 3 sec to 20 min and 2 x fixed at 3 sec |
| Horizontal pitch (HP): | 3 |
| Dimensions (mm) W x H x D: | 53.5 x 89 x 60 |

Article information

| Article designation | Article description | Colour/Material | Article no. |
|---------------------|------------------------------|-----------------|-------------|
| SFC 602-0 | Switching-/remote controller | Black | 015375 |



Switching-/remote
controller
SFC 602-0

Page 2

Accessories

| Article designation | Article description | Colour/Material | Article no. |
|---------------------|--------------------------|-----------------|-------------|
| ZAP 3-0 | Accessory terminal cover | Black | 113442 |

Switching-/remote
controller
SFC 602-0

Page 3





Switching-/remote
controller
SFC 602-0

Page 4

SFC 602-0 Switching / remote controller

Product information

429 kB

[Download](#)

SFC 602-...

Declaration of Conformity

13 kB

[Download](#)