

Door loudspeaker
controller
TLC 640-02

Page 1



Product description

Door loudspeaker controller in switch panel housing.

Control unit for all door loudspeaker functions.

- Terminal for door loudspeaker modules TLM 640-..., TLM 645-..., TLE 640-...
- 8 freely programmable inputs for call buttons and light buttons, for actuation of remote switching and signalling functions, for release of door release and door control times.
- 2 potential-free relay outputs as door release actuator or switching output for remote switching functions; programmable switching functions
- Interface to the Siedle Vario bus with connection facility for COM 611-... as call keypad or code lock module and DIM 640-... or DRM 611-... A maximum of 8 TME 640-... or TME 645-... units for connection of up to 500 direct call buttons. ELM 611-... for no-contact actuation of the door release via keycard or key. PRI 602-...and PRI 602-... USB port for programming via a PC/laptop.
- Display via control buttons for local programming, operator prompting and function display.

Specifications

Operating voltage:	24–28 V
Operating current:	350 mA
Contact type:	2 n.o. contacts 24 V, 1 A
Ambient temperature:	0 °C to +40 °C
Protection system:	IP 20
Horizontal pitch (HP):	6
Dimensions (mm) W x H x D:	107 x 89 x 60

Article information

Article designation	Article description	Colour/Material	Article no.
TLC 640-02	Door loudspeaker controller	Black	086500



Door loudspeaker
controller
TLC 640-02

Page 2

Accessories

Article designation	Article description	Colour/Material	Article no.
ZAP 6-0	Accessory terminal cover	Black	105205

Door loudspeaker
controller
TLC 640-02

Page 3





Door loudspeaker
controller
TLC 640-02

Page 4

	Product information	507 kB	Download
	Programming template	176 kB	Download
TLC 640-...	Declaration of Conformity	1,3 MB	Download